



complete **comfort**



LRP14AC
LRP14HP
LRP14GE
LRP14DF

Compact, efficient
packaged units

Comfort in all weather, in one streamlined package.

The LRP14 is the Lennox® packaged unit that does it all while sacrificing nothing. While it combines heating and cooling into one self-contained system, it never forgets that comfort is what it's all about.

The LRP14 is designed to be its best when the heat is at its worst. So your home remains a cool, refreshing escape even during the harshest heat. And you get peace of mind and comfort in any weather.

The LRP14 will also help you save on utility bills. Gas/electric, air conditioner, heat pump and dual-fuel models are available, with 14.00 SEER energy ratings.



Good things come in compact packages

Ideal for homes built on a crawlspace, instead of a basement, Lennox packaged units use the same components as a typical split system, but contain them all in one streamlined cabinet. Units can be installed on a rooftop or outside any home or office, connecting to your ductwork through a secure opening in the wall. This makes them easy to access for maintenance.

Utility savings without sacrifice

With efficiency ratings of 14.00 SEER/8.00 HSPF/81% AFUE, Lennox packaged units can deliver significant energy savings compared to older, less efficient units. You'll be able to lower your utility bills without compromising on comfort.

Quiet performance that's quite reliable

Standard on every Lennox packaged unit, an internally mounted outdoor fan helps reduce vibrations and keep operating sounds at a minimum, so you can enjoy uninterrupted peace and comfort.



designed for years of savings and **comfort**

Built for years of dependable comfort

Lennox packaged units are constructed from the highest quality materials to ensure season after season of reliable operation. Their rugged design includes steel louvered coil protection for added durability.

Peace-of-mind protection

The LRP14HP packaged heat pump and LRP14AC packaged air conditioner both come with a 10-year limited warranty on the compressor and a 10-year limited warranty* on remaining covered components. The LRP14GE packaged gas/electric unit and LRP14DF packaged dual-fuel both come with a 20-year limited warranty on the heat exchanger, a 10-year limited warranty on the compressor and a 10-year limited warranty* on remaining covered components.



*Online equipment registration at www.lennoxregistration.com is required within 60 days of installation (except in California and Quebec) or Lennox' base warranty will apply. Applies to residential applications only. See actual warranty certificate for details.

Lennox® LRP14 Packaged Units



Compact Design – Makes installation easy while leaving maximum useable indoor space.

Internally Mounted Outdoor Fan – Significantly reduces operating sound (vibrations).

Enhanced Coil Guard – Protects the condenser coil, maintaining the efficiency of the unit.

Easy Access Control Panel & Compressor Compartment – Allows faster servicing.

Efficient Blower Motor – Maximizes comfort and reliability.

Dependable Compressor – Provides years of proven comfort.

LRP14GE and LRP14DF only:

Tubular Heat Exchanger – Provides excellent heat transfer and superior airflow control for years of efficient, reliable operation.

LRP14AC Specifications

Model	24	30	36	42	48	60
SEER	14.00	14.00	14.00	14.00	14.00	14.00
Sound Rating (dB)	78	78	78	78	78	78
Dimensions HxWxD (in) HxWxD (mm)	36-7/8 x 46-3/4 x 46-3/4 937 x 1187 x 1187	36-7/8 x 46-3/4 x 46-3/4 937 x 1187 x 1187	36-7/8 x 46-3/4 x 46-3/4 937 x 1187 x 1187	40-7/8 x 55-1/4 x 46-3/4 1038 x 1403 x 1187	40-7/8 x 55-1/4 x 46-3/4 1038 x 1403 x 1187	40-7/8 x 55-1/4 x 46-3/4 1038 x 1403 x 1187

LRP14HP Specifications

Model	24	30	36	42	48	60
SEER	14.00	14.00	14.00	14.00	14.00	14.00
HSPF	8.00	8.00	8.00	8.00	8.00	8.00
Sound Rating (dB)	78	78	78	78	78	78
Dimensions HxWxD (in) HxWxD (mm)	36-7/8 x 46-3/4 x 46-3/4 937 x 1187 x 1187	36-7/8 x 46-3/4 x 46-3/4 937 x 1187 x 1187	36-7/8 x 46-3/4 x 46-3/4 937 x 1187 x 1187	40-7/8 x 55-1/4 x 46-3/4 1038 x 1403 x 1187	40-7/8 x 55-1/4 x 46-3/4 1038 x 1403 x 1187	40-7/8 x 55-1/4 x 46-3/4 1038 x 1403 x 1187

LRP14GE Specifications

Model	24	30	36	42	48	60
SEER	14.00	14.00	14.00	14.00	14.00	14.00
AFUE	81%	81%	81%	81%	81%	81%
Sound Rating (dB)	78	78	78	78	78	78
Dimensions HxWxD (in) HxWxD (mm)	36-7/8 x 46-3/4 x 46-3/4 937 x 1187 x 1187	36-7/8 x 46-3/4 x 46-3/4 937 x 1187 x 1187	36-7/8 x 46-3/4 x 46-3/4 937 x 1187 x 1187	40-7/8 x 55-1/4 x 46-3/4 1038 x 1403 x 1187	40-7/8 x 55-1/4 x 46-3/4 1038 x 1403 x 1187	40-7/8 x 55-1/4 x 46-3/4 1038 x 1403 x 1187

LRP14DF Specifications

Model	24	30	36	42	48	60
SEER	14.00	14.00	14.00	14.00	14.00	14.00
HSPF	8.00	8.00	8.00	8.00	8.00	8.00
AFUE	81%	81%	81%	81%	81%	81%
Sound Rating (dB)	78	78	78	78	78	78
Dimensions HxWxD (in) HxWxD (mm)	36-7/8 x 46-3/4 x 46-3/4 937 x 1187 x 1187	36-7/8 x 46-3/4 x 46-3/4 937 x 1187 x 1187	36-7/8 x 46-3/4 x 46-3/4 937 x 1187 x 1187	40-7/8 x 55-1/4 x 46-3/4 1038 x 1403 x 1187	40-7/8 x 55-1/4 x 46-3/4 1038 x 1403 x 1187	40-7/8 x 55-1/4 x 46-3/4 1038 x 1403 x 1187

Note: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change without notice.



For a complete list of the registered and common law trademarks owned by Lennox Industries Inc., please visit www.lennox.com.

